



FRAME ASSEMBLING MACHINE MODEL UP-M

A MANUAL BENCH MODEL OPERATED BY HYDRAULIC FOOT PEDAL



The **MORSØ-UP-M** is a manual bench model, which is operated by a single pressure on a hydraulic foot pedal. The **MORSØ UP-M** is perfect for the small shop, which does not have a lot of space. The **MORSØ-UP-M** can be placed almost everywhere, and does not require any kind of compressor or electricity.

Standard equipment for the machine:

- Two stops for min. and max. wedge position
- Single pressure pad for plain mouldings
- Two double pressure pads for mouldings with different profiles
- Adjustable fences - 90°, 60°, and 30° for rectangular, hexagonal and octagonal frames.
- Supports for long mouldings
- Two refill-able solid-steel cartridges for 7 and 10 mm wedges, respectively.
- Hydraulic foot pedal
- One box of 7 mm wedges (5000 pcs)
- One box of 10 mm wedges (3000 pcs)

ACCESSORIES:

Solid Steel cartridges

in 7 and 10 mm as standard.
Also available in 5 and 12 mm.



Two double Pressure Pads

one for mouldings with a standard profile and one for mouldings with a reversed profile. They are padded with synthetic fibres in order to leave no marks at all on the frame.



One flat pressure pad for mouldings with a plain surface. As with the double pressure pads, this one is also padded with synthetic fibres to protect the frame.



Wedges:

- 5 mm – 1 box 5000 pcs
- 7 mm – 1 box 5000 pcs
- 10 mm – 1 box 3000 pcs
- 12 mm – 1 box 3000 pcs

TECHNICAL DATA FOR MODEL UP-M

Wedge size	5, 7, 10 and 12 mm
Thickness of moulding, min.	6 mm (¼")
Thickness of moulding, max.	55 mm (2")
Width of moulding, min.	6 mm (¼")
Width of moulding, max.	105 mm (4")
Distance between wedges, max.	85 mm (3")
Height, Working Bench	176 mm (7")
Machine Dimension	335x240x420 mm
Length x Width x Height	(13x9½x16½")
Weight	25 kilos (55 lbs)